

GOLD FIELDS



GOLD FIELDS

CYANIDE OPTIMIZATION AND THE USE OF OZONE FOR WAD CYANIDE DESTRUCTION

South Deep Gold Mine

Metallurgical Plant

2009

Thulane Phiri

AGENDA



GOLD FIELDS

1. Introduction
2. Metallurgical Plant
3. ICMI Code and Implications
4. Initiatives
 - 4.1. Cyanide Reduction
 - 4.1.1. Oxidation Trial
 - 4.1.2. Two Stage cyanide control
 - 4.2. WAD Cyanide Destruction
 - 4.2.1. Hydrogen Peroxide (H₂O₂) Trial
 - 4.2.2. Ozone Trial
5. Conclusion

1. INTRODUCTION



GOLD FIELDS

- Gold Fields South Deep is Located in the South West Rand
- New gold plant was commissioned in 2002
- Design capacity of 220 000 t/month
- The mining method by Trackless mining
- Gold recovery achieved by Milling, Classification (cyclones), Gravity gold, Thickening, Leaching, CIP, Elution, Electro-wining and Smelting


2. METALLURGICAL PLANT



GOLD FIELDS



SOUTH DEEP GOLD PLANT PROCESS FLOW



3. ICMI CODE AND IMPLICATIONS



- In the year 2000 the ICMI (International Cyanide Management Institute) Code was developed after an accidents in *Baia Mare*
- Mines that are compliant with the ICMI code they have to implement the Principles and Standard of practice
 - *Production*
 - *Transportation*
 - *Handling and storage*
 - *Operation*
 - *Decommissioning*
 - *Workers safety*
 - *Emergency response*
 - *Training*
 - *Dialogue*




- Gold Fields South Deep Gold Mine has been certified as fully compliant with the ICMI Code as from the 1 April 2009
- The Metallurgical Plant had to demonstrate that it has implement programs, procedures and practises as required by ICMI
- Principle 4: **Standard of Practice 4.2 of the code “*Has the operation introduced management and operating systems to minimize cyanide use, thereby limiting concentrations of cyanide in mill tailings*”**
- **Standard of Practice 4.6.3 “*Has the potential impacts to workers health and the beneficial uses of ground water been evaluated and have been measures been implemented as necessary to address them?*”**

Cyanide Addition and Monitoring



GOLD FIELDS



Areas of concern (Underground and Slimes dam)



GOLD FIELDS



- Possibility of HCN gassing
- No CN monitors
- “Cyanide tracking underground as a function of backfill seepage”

P. W. Lotz

Cyanide Addition



GOLD FIELDS

TAC 2000

- Leach TK 1
- TK1 Cyanide addition Set Point 200ppm
- TK4 Cyanide addition Set Point 90ppm



WAD Cyanide Monitoring



GOLD FIELDS

WAD 1000 (Plant and Backfill)

- Pump
- Probe at Tailings Sump
- Analyser for Analysis and Data collection



4. INITIATIVES

4.1. CYANIDE REDUCTION




4.1.1. Oxidation Trial





GOLD FIELDS

- Oxygen from Air Products was used to improve
 - Recoveries
 - Leach kinetics
 - Dissolved oxygen levels
 - Lower cyanide consumption
- First phase of the trial
 - Oxygen added in TK 1 together with cyanide and lime
- Second phase
 - Pre-Oxidation in TK 1 leach tank prior to adding cyanide and Lime in TK 2









- The DO level during P1 was <4.2ppm and during P2 the DO levels increased in TK 1 and TK 2 to 10.02ppm and 7.16ppm



- Cyanide consumption during P1 was 0.366kg/t and was 0.270kg/t during P2



- During P1 and P2 there was a rapid increase in dissolution of gold within the first three tanks which resulted in increased leach kinetics



- The increase in residue resulted in increase cyanide set point
- During P2 residues dropped for both solution and washed solids and that resulted in cyanide addition set points from 350ppm to 180ppm




- Phase 1 results
 - Oxygen trial improved
 - Dissolved Oxygen levels
 - No changes in cyanide consumption
 - Leach profiles indicated faster leach kinetics

- Phase 2 results
 - Pre-oxidation resulted in reduction in cyanide consumption from 0.366 kg/t to 0.270kg/t
 - Increased leach kinetics
 - Dissolved oxygen levels
 - Leach could be operated with less tanks resulting in reduction in gold lock up and maintenance cost
 - Cyanide set point was reduced from 350ppm to 180ppm



4.1.2. Two Stage cyanide control

- The aim
 - Optimize the cyanide addition at the Leach circuit
 - To reduce cyanide cost
 - Reducing the WAD cyanide leaving the Plant to < 50ppm as required by the ICMI
- The cyanide is dosed at TK 1 using TAC 2000
 - Cyanide set point in TK 1 is 200ppm and at TK 4 is 90ppm
 - The WAD Cyanide leaving the Plant is currently 28ppm which is below ICMI requirement of 50ppm WAD



- TK 4 has been identified as the cyanide second stage addition point
- The installation of the second stage at TK 4 has been completed
- The cyanide reduction should impact the WAD cyanide to levels lower than 28ppm thus reducing cyanide consumption and cost



4.2. WAD CYANIDE DESTRUCTION



GOLD FIELDS

4.2.1. Hydrogen Peroxide (H₂O₂) Trial

- The aim
 - Determine the effectiveness of Hydrogen peroxide (H₂O₂) with regard to WAD cyanide destruction to levels <20ppm
 - Determine if Hydrogen peroxide could be used as an alternative to Ferrous sulphate that is currently used



- The test works were done Plant scale and Lab scale







Table 2: WAD destruction results summary using Hydrogen Peroxide


	Test 1	Test 2	Test 3	Test 4	Test5
Density of Slurry (kg/l)	1.82	1.6	1.75	1.75	1.92
Volume of Slurry (l)	215000	5	5	5	96000
Mass of Slurry (kg)	391300	8	8.75	8.75	184320
Density of Hydrogen peroxide (kg/l)	1.2	1.2	1.2	1.2	1.2
Volume of Hydrogen peroxide (l)	150	0.5	0.05	0.01	200
Mass of Hydrogen peroxide (kg)	180	0.6	0.06	0.012	240
Consumption (kg/t)	0.46	75.00	6.86	1.37	1.30
Duration (hr)	32	2	2	2	2
WAD first value (ppm)	52.8	19.6	23.6	21.6	31.5
WAD Last value (ppm)	20.1	0.1	2.7	4.3	3.3
Efficiency	61.9	99.5	88.6	80.1	89.52
Cost per ton (R/t)	3.86	629.38	57.54	11.51	10.93



GOLD FIELDS



- The results indicates that WAD cyanide was best reduced in Test 2 followed by 3 and 4 although Hydrogen peroxide consumption was high for Test 2, 3 than 4



- Hydrogen Peroxide does reduce the WAD cyanide levels to <5ppm in 2 hours






- It was concluded
 - Hydrogen Peroxide does reduce the WAD cyanide levels to even <5ppm effectively
 - Hydrogen Peroxide can be used as an alternative to ferrous sulphate
- It was recommended
 - Attempts be made to lower consumptions to minimize operational cost
 - WAD Cyanide be destroyed at Metallurgical Plant Tailings to levels <50ppm



4.2.2. Ozone Trial

- The cyanide destruction using Ozone is done to reduce the WAD cyanide leaving the Plant to Slimes dam and Underground
- The Ozone is a powerful oxidant and highly destructive toward WAD cyanide according to Lab test results




- These are initiatives taken to protect the people and the environment



GOLD FIELDS

Ozone skid/generation



GOLD FIELDS



VSA Generator



Oxygen Buffer Vessel



WEDECO Ozone Generator



Mixing vessel




- The Ozone Trial was planned for 3 months at following streams
 - Backfill Tailings to Slime dam
 - Backfill to underground
 - Ultracep underflow
 - Ultracep overflow
 - Spent sample
- WAD cyanide was analysed using WAD 1000


Achievement



GOLD FIELDS



Relationship between Power (W) and Power consumption % is linear




Power consumption %	Ozone concentration (g/m ³)
20	24
40	44
60	59
80	73
100	80

Relationship between Power consumption % and Ozone concentration



% WAD CN in Tailing Sample




- WAD cyanide reduction of 98.7% for the slurry pumped from Backfill Tailings to Slimes dam at 60% power consumption



GOLD FIELDS


Average Ultracept Underflow % WAD CN



- Ultracept underflow WAD cyanide was reduced by 94.6% at 60% power consumption



Average Ultracorp Overflow Material WAD CN %




- Ultracorp overflow WAD cyanide was reduced by 94.7% at 20% power consumption



GOLD FIELDS

Average Underground Material WAD CN %




- Backfill to underground WAD cyanide was reduced by 94.5% at 60% power consumption

GOLD FIELDS



Spent Electrolyte %WAD CN



•Spent sample WAD cyanide was reduced by 92% at 80% power consumption



- Ozone trial was successful in WAD cyanide destruction for all the streams tested as >92% destruction at optimum condition
- Alternative method to destroy WAD cyanide
- WAD levels < 50ppm at all times



Advantages of the ozone includes

- Rapid WAD cyanide destruction
- No formation of harmful off gases

Cost

- Operating cost associated with ozone to be further investigated

5. CONCLUSION



GOLD FIELDS

- South Deep has achieved WAD <50ppm
- Compliant with the ICMI Code
- Reduced and maintained cyanide addition levels from 0.366kg/t to 0.270kg/t
- Initiatives successful in WAD cyanide destruction to lower levels
- Alternative in both cyanide reduction and WAD cyanide destruction
- Prepared for the future changes in legislation

GOLD FIELDS



GOLD FIELDS

QUESTIONS?